



Dudhi Gypsum Plaster Bond

No hacking no wire mesh no de-bondinggo for Dudhi Plaster Bond.

Dudhi Gypsum Plaster Bond is a bonding agent suitable to Gypsum Base plasters for the internal plastering with low suction background as RCC re- in forced cement wall and any other smooth hard surface. It provides extra bonding in both ways as chemically adhesion and mechanical key as required to the Gypsum base plasters on smooth and low suction background. A single coat brush application is sufficient to get required bonding with this product.

Basic features of the Product

- Base : Reign and fine aggregates.
Colour : Green colour to easily identify coating area.
Back Ground : This product is most suitable to RCC walls/ ceiling, re-in forced mortar wall along with Other hard smooth surface.
Soluble : water.
Application : By paint Brush.
Coverage : Aprox 5-6 m² /kg.
pH Value : 8-10

Tips to use:-

- The surface to be coated should be free from dust, wetness, loose particles and mould oil.
- Stir well before use the adhesive as the settled grains mix properly.
- Apply the plaster bond by wider paint brush as the aggregates should be formed a textured finish in random pattern on the surface along with thin coating.
- Any type of Gypsum plaster can be applied after drying the coating. The drying time is approx 20-24 hours.
- The coated surface should be plastered within 10-15 days to avoid damage of coating or accomplished of dust particles on the surface.
- If Bond application did more than 1 to 2 Months and the surface to be coated is not free from dust, wetness, loose particles, and mould oil then it should be clean with a brush, cloths or air and broom. No need to again apply plaster bond.
- If you will apply the 2nd layer on that then plaster bond thickness will be high then possible plaster could be debonding.
- If not possible to remove dust then you have 2nd option is, earlier plaster bond you have to remove, and again you have to apply.
- The thickness of plaster can be made 10-15 mm maximum with this bond.

Pre cautions:-

- The surface to be plastered not to be hacked and No wire mesh put on as re-enforcements.
- No Post / Pre- Curing to be made for the application.
- Before coating the surface should be dry and free from loose particles.
- Do not over coat as the uniform thin coat is sufficient for the adhesion.
- Do not waste/ through the aggregate during the application.

Packing & Self Life:-

Dudhi Plaster Bonding is available in plastic bucket size of 10 & 20kg. The Self life is approximately 6 Months from date of manufacturer

दुद्धी इण्डस्ट्रीज प्राइवेट लिमिटेड

F-238,239, प्रथम तल, टावर - बी, पालम कॉरपोरेट प्लाजा, ब्लॉक -C2 पालम विहार, गुरुग्राम - 122 001 (हरियाणा)
t 0124-4830680, 9560393000, 9560393009 e info@dudhi.in w www.dudhi.in

फैक्टरी I : M.No.- 56/4, Chak 6PRM, पुगल रोड, दनतोर, तहसील - खाजुवाला, जिला - बीकानेर - 334004 (राजस्थान)
फैक्टरी II : खसरा नं. - 60, नौरंगापुर - सिलाना रोड, गाँव - सिलाना, तहसील - झज्जर, जिला - झज्जर - 124103 (हरियाणा)