

Dudhi Crack Filler is a gypsum-based product for filling cracks and cavities in walls. Dudhi Crack Filler contains a Polymers, Fillers & Extenders, Dispersing Agents, cellulose derivative, which improves cohesive strength and promotes adhesion to ceiling boards, plaster, lime, cement.



► Technical Specification

Parameter	Dudhi Gypsum Crack Filler
Type	Gypsum Based
Setting Time (Min)	25-30
Moisture Resistance	Good
Wet Bulk Density	1.40 – 1.60 gm/cm ³

► Features

- Low shrinkage -fills up to 1 mm - 2mm gaps
- Good anti-slump / non-sag properties – easily applied to vertical surfaces
- Excellent workability – easy to spread and smooth
- Paintable in 3 hours – can complete the job quickly
- White finish – less tendency to show through after painting
- High strength – can hold screws without cracking
- Good sanding and painting properties – easy to achieve desired finish Applications Filling cracks, slits, cavities and gaps on walls. Also used as a skimming agent for the smoothing of irregular wall surfaces.

► Application

- Smooth cracked area with a utility knife or similar tool, cutting away any jagged edges to form a “v” shape
- Excess crack filler must be worked away from the crack and smoothed off with a lightly wetted putty knife or trowel to avoid any excess crack filler from hardening in undesirable areas
- Clean the putty knife regularly with a damp cloth, which will ensure a smooth lump-free finish
- All repaired cracks must be allowed to dry for 3 hours before sanding and painting



► Useful Tips

- Add upto 3 parts of crack filler to 1 part of clean cold water (to form workable consistency).
- Mix to a smooth lump free paste
- Do not mix more paste than can be used within 30 minutes
- Use an 80-100mm wide flexible putty knife to feather the edges of the patch to approximately 30mm on either side of the crack. This will make the crack less noticeable to the eye.
- Dudhi Crack Filler adhesive must be kept in normal, dry conditions and protected from damp. The product has a shelf life of approximately 9 months if stored, as described above, in its original sealed moisture tight container
- Not suitable for repairing of structural faults (foundation movements and substrate)
- Not suitable for external use
- Dudhi Interior Crack Filler contains no harmful materials but may cause skin irritation to some individuals. Do not ingest and avoid contact with eyes.

