



DUDHI CRACKFILLER

Description

DUDHI CRACKFILLER is a gypsum-based product for filling cracks and cavities in walls. It can also be used as a skimming material to give a smooth surface prior to painting.

DUDHI CRACKFILLER contains a Polymers, Fillers & Extenders, Dispersing Agents, cellulose derivative, which improves cohesive strength and promotes adhesion to ceiling boards, plaster, lime, cement.

Features & Benefits

- Low shrinkage -fills up to 1mm gaps
 - Good anti-slump / non-sag properties – easily applied to vertical surfaces
 - Excellent workability – easy to spread and smooth
 - Paintable in 3 hours – can complete the job quickly
 - White finish – less tendency to show through after painting
 - High strength – can hold screws without cracking
 - Good sanding and painting properties – easy to achieve desired finish
- Applications Filling cracks, slits, cavities and gaps on walls. Also used as a skimming agent for the smoothing of irregular wall surfaces.

Limitations

- Not suitable for repairing of structural faults (foundation movements and substrate)
- Not suitable for repairing cracks on flexible surfaces – use a more flexible crack filler such as DUDHI FLEXIFILL
- Not suitable for external use

Safety instructions

DUDHI INTERIOR CRACKFILLER contains no harmful materials but may cause skin irritation to some individuals. Do not ingest. Keep away from children and pets. Do not empty into drains. Wear rubber gloves. Avoid contact with eyes. Allow any unused product to dry before disposing of the container. In the event of skin or eye contamination, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort persists. Refer to our Material Safety Data Sheets for further toxicological information and comprehensive handling instructions

दुध्नी इण्डस्ट्रीज प्राइवेट लिमिटेड

F-238,239, प्रथम तल, टावर – बी, पालम कॉरपोरेट प्लाजा, ब्लॉक –C2 पालम विहार, गुरुग्राम – 122 001 (हरियाणा)
t 0124-4830680, 9560393000, 9560393009 e info@dudhi.in w www.dudhi.in

फैक्टरी I : M.No.- 56/4, Chak 6PRM, पुगल रोड, दनतोर, तहसील – खाजुवाला, जिला – बीकानेर – 334004 (राजस्थान)
फैक्टरी II : खसरा नं. – 60, नौरंगपुर – सिलाना रोड, गाँव – सिलाना, तहसील – झज्जर, जिला – झज्जर – 124103 (हरियाणा)



Directions for use Surface preparation

1. Ensure surfaces to be filled are clean, dry and free of dust and grease
2. Smooth cracked area with a utility knife or similar tool, cutting away any jagged edges to form a “v” shape
3. Narrow cracks - dampen the area first with a spray bottle and water. Hairline cracks, small blemishes and indentations should be widened using the above procedure.

Mixing

1. Add ± 3 parts of crack filler to 1 part of clean cold water by volume
2. Mix to a smooth lump free paste
3. Do not mix more paste than can be used within 30 minutes

Application

1. Apply crack filler to the surface to be filled and work it into the crack with a lightly wetted putty knife or trowel. Ensure that the crack is completely filled.
 2. Excess crack filler must be worked away from the crack and smoothed off with a lightly wetted putty knife or trowel to avoid any excess crack filler from hardening in undesirable areas
 3. Clean the putty knife regularly with a damp cloth, which will ensure a smooth lump-free finish
 4. All repaired cracks must be allowed to dry for 3 hours before sanding and painting
- Useful tip: Use an 80-100mm wide flexible putty knife to feather the edges of the patch to approximately 30mm on either side of the crack. This will make the crack less noticeable to the eye. Note using a smaller knife will tend to gouge the substrate Cleaning Tools can be cleaned with water and soap when adhesive is still wet.

Storage stability

DUDHI CRACKFILLER adhesive must be kept in normal, dry conditions and protected from damp. The product has a shelf life of approximately 9 months if stored, as described above, in its original sealed moisture tight container.

PHYSICAL DATA

Type	GYPSUM BASED
MOISTURE RESISTANCE	GOOD
Mixed weight	± 1.5 kg per litre

दुद्धी इन्डस्ट्रीज प्राइवेट लिमिटेड

F-238,239, प्रथम तल, टावर - बी, पालम कॉरपोरेट प्लाजा, ब्लॉक -C2 पालम विहार, गुरुग्राम - 122 001 (हरियाणा)
t 0124-4830680, 9560393000, 9560393009 e info@dudhi.in w www.dudhi.in

फैक्टरी I : M.No.- 56/4, Chak 6PRM, पुगल रोड, दनतोर, तहसील - खाजुवाला, जिला - बीकानेर - 334004 (राजस्थान)
फैक्टरी II : खसरा नं. - 60, नौरंगपुर - सिलाना रोड, गाँव - सिलाना, तहसील - झज्जर, जिला - झज्जर - 124103 (हरियाणा)